

# Machine Learning & Data Mining

## CS/CNS/EE 155

Lecture 3:  
Regularization, Sparsity & Lasso

# Homework 1

- Check course website!
- Some coding required
- Some plotting required
  - I recommend Matlab
- Has supplementary datasets
- Submit via Moodle (due Jan 20<sup>th</sup> @5pm)

# Recap: Complete Pipeline

$$S = \{(x_i, y_i)\}_{i=1}^N$$


Training Data

$$f(x | w, b) = w^T x - b$$

Model Class(es)

$$L(a, b) = (a - b)^2$$

Loss Function



$$\operatorname{argmin}_{w,b} \sum_{i=1}^N L(y_i, f(x_i | w, b))$$

Cross Validation & Model Selection



Profit!

# Different Model Classes?

- Option 1: SVMs vs ANNs vs LR vs LS
- Option 2: Regularization



$$\operatorname{argmin}_{w,b} \sum_{i=1}^N L(y_i, f(x_i | w, b))$$

Cross Validation & Model Selection

# Notation

- L0 Norm

- # of non-zero entries

$$\|w\|_0 = \sum_d 1_{[w_d \neq 0]}$$

- L1 Norm

- Sum of absolute values

$$|w| = \|w\|_1 = \sum_d |w_d|$$

- L2 Norm & Squared L2 Norm

- Sum of squares
  - Sqrt(sum of squares)

$$\|w\| = \sqrt{\sum_d w_d^2} \equiv \sqrt{w^T w}$$

$$\|w\|^2 = \sum_d w_d^2 \equiv w^T w$$

- L-infinity Norm

- Max absolute value

$$\|w\|_\infty = \lim_{p \rightarrow \infty} \sqrt[p]{\sum_d |w_d|^p} = \max_d |w_d|$$

# Notation Part 2

- Minimizing Squared Loss
  - Regression
  - Least-Squares
  - (Unless Otherwise Stated)
    - E.g., Logistic Regression = Log Loss


$$\operatorname{argmin}_w \sum_i (y_i - w^T x + b)^2$$

# Ridge Regression

$$\operatorname{argmin}_{w,b} \lambda w^T w + \sum_i (y_i - w^T x + b)^2$$

The diagram shows the cost function for Ridge Regression. It consists of two main parts: a regularization term and a training loss term. The regularization term is represented by a blue bracket under the term  $\lambda w^T w$ . The training loss term is represented by a blue bracket under the sum  $\sum_i (y_i - w^T x + b)^2$ . Below the first bracket is the label "Regularization" and below the second bracket is the label "Training Loss".

- aka L2-Regularized Regression
- Trades off model complexity vs training loss
- Each choice of  $\lambda$  a “model class”
  - Will discuss the further later



$$\operatorname{argmin}_{w,b} \lambda w^T w + \sum_i (y_i - w^T x + b)^2$$

	w		b
0.7401	0.2441	-0.1745	
0.7122	0.2277	-0.1967	
0.6197	0.1765	-0.2686	
0.4124	0.0817	-0.4196	
0.1801	0.0161	-0.5686	
	⋮		
0.0001	0.0000	-0.6666	

Larger Lambda

Person	Age>10	Male?	Height > 55"
Alice	1	0	1
Bob	0	1	0
Carol	0	0	0
Dave	1	1	1
Erin	1	0	1
Frank	0	1	1
Gena	0	0	0
Harold	1	1	1
Irene	1	0	0
John	0	1	1
Kelly	1	0	1
Larry	1	1	1

Train

Test

# Updated Pipeline

$$S = \{(x_i, y_i)\}_{i=1}^N$$

Training Data

$$f(x | w, b) = w^T x - b$$

Model Class

$$L(a, b) = (a - b)^2$$

Loss Function



$$\operatorname{argmin}_{w,b} \lambda w^T w + \sum_{i=1}^N L(y_i, f(x_i | w, b))$$

Choosing  $\lambda$ !

Cross Validation & Model Selection







Profit!

Person	Age>10	Male?	Height > 55"	Model Score w/ Increasing Lambda					
				0.91	0.89	0.83	0.75	0.67	
Train	Alice	1	0	1	0.91	0.89	0.83	0.75	0.67
	Bob	0	1	0	0.42	0.45	0.50	0.58	0.67
	Carol	0	0	0	0.17	0.26	0.42	0.50	0.67
	Dave	1	1	1	1.16	1.06	0.91	0.83	0.67
	Erin	1	0	1	0.91	0.89	0.83	0.79	0.67
	Frank	0	1	1	0.42	0.45	0.50	0.54	0.67
Test	Gena	0	0	0	0.17	0.27	0.42	0.50	0.67
	Harold	1	1	1	1.16	1.06	0.91	0.83	0.67
	Irene	1	0	0	0.91	0.89	0.83	0.79	0.67
	John	0	1	1	0.42	0.45	0.50	0.54	0.67
	Kelly	1	0	1	0.91	0.89	0.83	0.79	0.67
	Larry	1	1	1	1.16	1.06	0.91	0.83	0.67

Best test error

# Choice of Lambda Depends on Training Size



25 dimensional space

Randomly generated linear response function + noise

# Recap: Ridge Regularization

- Ridge Regression:
  - L2 Regularized Least-Squares

$$\operatorname{argmin}_{w,b} \lambda w^T w + \sum_i (y_i - w^T x + b)^2$$

- Large  $\lambda \rightarrow$  more stable predictions
  - Less likely to overfit to training data
  - Too large  $\lambda \rightarrow$  underfit
- Works with other loss
  - Hinge Loss, Log Loss, etc.

# Model Class Interpretation


$$\operatorname{argmin}_{w,b} \lambda w^T w + \sum_{i=1}^N L(y_i, f(x_i | w, b))$$

- This is not a model class!
  - At least not what we've discussed...
- An optimization procedure
  - Is there a connection?

# Norm Constrained Model Class


$$f(x | w, b) = w^T x - b \quad \text{s.t. } w^T w \leq c \equiv \|w\|^2 \leq c$$

Visualization




Seems to correspond to lambda...

$$\operatorname{argmin}_{w,b} \lambda w^T w + \sum_{i=1}^N L(y_i, f(x_i | w, b))$$



# Lagrange Multipliers

$$\underset{w}{\operatorname{argmin}} L(y, w) \equiv (y - w^T x)^2$$



- Optimality Condition:
  - Gradients aligned!
  - Constraint Boundary
  - Loss

$$\exists \lambda \geq 0 : (\partial_w L(y, w) = \lambda \partial_w w^T w) \wedge (w^T w \leq c)$$

Omitting b &  
1 training data  
for simplicity

### Norm Constrained Model Class Training:

$$\underset{w}{\operatorname{argmin}} L(y, w) = (y - w^T x)^2 \quad \text{s.t. } w^T w \leq c$$

Omitting b &  
1 training data  
for simplicity

Two Conditions  
Must Be Satisfied  
At Optimality  $\Leftrightarrow$ .

### Observation about Optimality:

$$\exists \lambda \geq 0 : (\partial_w L(y, w) = \lambda \partial_w w^T w) \wedge (w^T w \leq c)$$

### Lagrangian:

$$\underset{w, \lambda}{\operatorname{argmin}} \Lambda(w, \lambda) = (y - w^T x)^2 + \lambda (w^T w - c)$$

Claim: Solving Lagrangian  
Solves Norm-Constrained  
Training Problem

Satisfies First Condition!

### Optimality Implication of Lagrangian:

$$\begin{aligned} \partial_w \Lambda(w, \lambda) &= -2x(y - w^T x)^T + 2\lambda w \equiv 0 \\ \Rightarrow 2x(y - w^T x)^T &= 2\lambda w \end{aligned}$$

### Norm Constrained Model Class Training:

$$\underset{w}{\operatorname{argmin}} L(y, w) = (y - w^T x)^2 \quad \text{s.t. } w^T w \leq c$$

Omitting b &  
1 training data  
for simplicity

Two Conditions  
Must Be Satisfied  
At Optimality  $\Leftrightarrow$ .

### Observation about Optimality:

$$\exists \lambda \geq 0 : (\partial_w L(y, w) = \lambda \partial_w w^T w) \wedge (w^T w \leq c)$$

### Lagrangian:

$$\underset{w, \lambda}{\operatorname{argmin}} \Lambda(w, \lambda) = (y - w^T x)^2 + \lambda (w^T w - c)$$

**Claim:** Solving Lagrangian  
Solves Norm-Constrained  
Training Problem

### Optimality Implication of Lagrangian:

Satisfies 2<sup>nd</sup>  
Condition!

$$\partial_\lambda \Lambda(w, \lambda) = \begin{cases} 0 & \text{if } w^T w < c \\ w^T w - c & \text{if } w^T w \geq c \end{cases} \equiv 0 \rightarrow w^T w \leq c$$

### Norm Constrained Model Class Training:

$$\operatorname{argmin}_w L(y, w) \equiv (y - w^T x)^2 \quad \text{s.t. } w^T w \leq c$$

### L2 Regularized Training:

$$\operatorname{argmin}_w \lambda w^T w + (y - w^T x)^2$$

### Lagrangian:

$$\operatorname{argmin}_{w,\lambda} \Lambda(w, \lambda) = (y - w^T x)^2 + \lambda (w^T w - c)$$

- Lagrangian = Norm Constrained Training:

$$\exists \lambda \geq 0 : (\partial_w L(y, w) = \lambda \partial_w w^T w) \wedge (w^T w \leq c)$$

- Lagrangian = L2 Regularized Training:

- Hold  $\lambda$  fixed

- Equivalent to solving Norm Constrained!

- For some  $c$

Omitting b &  
1 training data  
for simplicity

# Recap #2: Ridge Regularization

- Ridge Regression:
  - L2 Regularized Least-Squares = Norm Constrained Model
$$\operatorname{argmin}_{w,b} \lambda w^T w + L(w) \quad \equiv \quad \operatorname{argmin}_{w,b} L(w) \text{ s.t. } w^T w \leq c$$
- Large  $\lambda \rightarrow$  more stable predictions
  - Less likely to overfit to training data
  - Too large  $\lambda \rightarrow$  underfit
- Works with other loss
  - Hinge Loss, Log Loss, etc.

# Hallucinating Data Points

$$\operatorname{argmin}_w \lambda w^T w + \sum_{i=1}^N (y_i - w^T x_i)^2$$

$$\partial_w = 2\lambda w - 2 \sum_{i=1}^N x (y_i - w^T x_i)^T$$

- Instead hallucinate D data points?

$$\operatorname{argmin}_w \sum_{d=1}^D (0 - w^T \sqrt{\lambda} e_d)^2 + \sum_{i=1}^N (y_i - w^T x_i)^2$$

$$\partial_w = 2 \sum_{d=1}^D \sqrt{\lambda} e_d (w^T \sqrt{\lambda} e_d)^T - 2 \sum_{i=1}^N x (y_i - w^T x_i)^T$$

$$= 2 \sum_{d=1}^D \lambda e_d^T w = 2 \sum_{d=1}^D \lambda w_d = 2\lambda w$$

**Identical to  
Regularization!**

$$\left\{ (\sqrt{\lambda} e_d, 0) \right\}_{d=1}^D$$

Unit vector  
along d-th  
Dimension

$$e_d = \begin{bmatrix} 0 \\ \vdots \\ 0 \\ 1 \\ 0 \\ \vdots \\ 0 \end{bmatrix}$$

Omitting b &  
for simplicity

# Extension: Multi-task Learning

- 2 prediction tasks:
  - Spam filter for Alice
  - Spam filter for Bob
- Limited training data for both...
  - ... but Alice is similar to Bob

# Extension: Multi-task Learning

- Two Training Sets
  - N relatively small
- **Option 1:** Train Separately

$$\underset{w}{\operatorname{argmin}} \lambda w^T w + \sum_{i=1}^N (y_i^{(1)} - w^T x_i^{(1)})^2$$

$$S^{(1)} = \left\{ (x_i^{(1)}, y_i^{(1)}) \right\}_{i=1}^N$$

$$S^{(2)} = \left\{ (x_i^{(2)}, y_i^{(2)}) \right\}_{i=1}^N$$

Both models have high error.

$$\underset{v}{\operatorname{argmin}} \lambda v^T v + \sum_{i=1}^N (y_i^{(2)} - v^T x_i^{(2)})^2$$

Omitting b &  
for simplicity

# Extension: Multi-task Learning

- Two Training Sets
  - N relatively small
- **Option 2:** Train Jointly

$$\begin{aligned} \operatorname{argmin}_{w,v} & \lambda w^T w + \sum_{i=1}^N \left( y_i^{(1)} - w^T x_i^{(1)} \right)^2 \\ & + \lambda v^T v + \sum_{i=1}^N \left( y_i^{(2)} - v^T x_i^{(2)} \right)^2 \end{aligned}$$

$$S^{(1)} = \left\{ (x_i^{(1)}, y_i^{(1)}) \right\}_{i=1}^N$$

$$S^{(2)} = \left\{ (x_i^{(2)}, y_i^{(2)}) \right\}_{i=1}^N$$

Doesn't accomplish anything!  
(w & v don't depend on each other)

Omitting b &  
for simplicity


# Multi-task Regularization

$$\underset{w,v}{\operatorname{argmin}} \lambda w^T w + \lambda v^T v + \gamma (w - v)^T (w - v) + \sum_{i=1}^N (y_i^{(1)} - w^T x_i^{(1)})^2 + \sum_{i=1}^N (y_i^{(2)} - v^T x_i^{(2)})^2$$



Standard Regularization      Multi-task Regularization      Training Loss

- Prefer  $w$  &  $v$  to be “close”
  - Controlled by  $\gamma$
  - Tasks similar
    - Larger  $\gamma$  helps!
  - Tasks not identical
    - $\gamma$  not too large



# Lasso

## L1-Regularized Least-Squares

# L1 Regularized Least Squares

$$\operatorname{argmin}_w \lambda |w| + \sum_{i=1}^N (y_i - w^T x_i)^2$$

$$\operatorname{argmin}_w \lambda \|w\|^2 + \sum_{i=1}^N (y_i - w^T x_i)^2$$

- L2:

$$w = \sqrt{2} \quad \text{vs} \quad w = 1$$

||


$$w = 1 \quad \text{vs} \quad w = 0$$

- L1:

$$w = 2 \quad \text{vs} \quad w = 1$$

||

$$w = 1 \quad \text{vs} \quad w = 0$$



Omitting b &  
for simplicity

# Subgradient (sub-differential)


$$\nabla_a R(a) = \{c \mid \forall a' : R(a') - R(a) \geq c(a' - a)\}$$

- Differentiable:  $\nabla_a R(a) = \partial_a R(a)$

- L1:

$$\nabla_{w_d} |w| \begin{cases} -1 & \text{if } w_d < 0 \\ +1 & \text{if } w_d > 0 \\ [-1, +1] & \text{if } w_d = 0 \end{cases}$$

Continuous range for  $w=0$ !



Omitting b &  
for simplicity

# L1 Regularized Least Squares

$$\operatorname{argmin}_w \lambda |w| + \sum_{i=1}^N (y_i - w^T x_i)^2$$


$$\operatorname{argmin}_w \lambda \|w\|^2 + \sum_{i=1}^N (y_i - w^T x_i)^2$$

- L2:

$$\nabla_{w_d} \|w\|^2 = 2w_d$$

- L1:

$$\nabla_{w_d} |w| \begin{cases} -1 & \text{if } w_d < 0 \\ +1 & \text{if } w_d > 0 \\ [-1, +1] & \text{if } w_d = 0 \end{cases}$$




Omitting b &  
for simplicity

# Lagrange Multipliers

$$\underset{w}{\operatorname{argmin}} L(y, w) \equiv (y - w^T x)^2$$

$$\text{s.t. } |w| = c$$

$$\nabla_{w_d} |w| \begin{cases} -1 & \text{if } w_d < 0 \\ +1 & \text{if } w_d > 0 \\ [-1, +1] & \text{if } w_d = 0 \end{cases}$$



$$\exists \lambda \geq 0 : (\partial_w L(y, w) \in \lambda \nabla_w |w|) \wedge (|w| \leq c)$$

Omitting b &  
1 training data  
for simplicity

# Sparsity

- $w$  is sparse if mostly 0's:
  - Small L0 Norm

$$\|w\|_0 = \sum_d 1_{[w_d \neq 0]}$$

- Why not L0 Regularization?

- **Not continuous!**

$$\operatorname{argmin}_w \lambda \|w\|_0 + \sum_{i=1}^N (y_i - w^T x_i)^2$$

- L1 induces sparsity
  - And is continuous!

$$\operatorname{argmin}_w \lambda |w| + \sum_{i=1}^N (y_i - w^T x_i)^2$$

Omitting b &  
for simplicity

# Why is Sparsity Important?

- Computational / Memory Efficiency
  - Store 1M numbers in array
  - Store 2 numbers per non-zero
    - (Index, Value) pairs
    - E.g., [ (50,1), (51,1) ]
  - Dot product more efficient:  $w^T x$
- Sometimes true w is sparse
  - Want to recover non-zero dimensions

$$\begin{bmatrix} 0 \\ 0 \\ \vdots \\ 0 \\ 1 \\ 1 \\ 0 \\ \vdots \\ 0 \end{bmatrix}$$

# Lasso Guarantee

$$\operatorname{argmin}_w \lambda |w| + \sum_{i=1}^N (y_i - w^T x_i + b)^2$$

- Suppose data generated as:  $y_i \sim Normal(w_*^T x_i, \sigma^2)$
- Then if:  $\lambda > \frac{2}{\kappa} \sqrt{\frac{2\sigma^2 \log D}{N}}$
- With high probability (increasing with N):

$$Supp(w) \subseteq Supp(w_*)$$


High Precision  
Parameter Recovery

$$\forall d : |w_d| \geq \lambda c \rightarrow Supp(w) = Supp(w_*)$$

Sometimes High Recall

$$Supp(w_*) = \{d | w_{*,d} \neq 0\}$$

See also: <https://www.cs.utexas.edu/~pradeepr/courses/395T-LT/filez/highdimII.pdf>  
[http://www.eecs.berkeley.edu/~wainwrig/Papers/Wai\\_SparseInfo09.pdf](http://www.eecs.berkeley.edu/~wainwrig/Papers/Wai_SparseInfo09.pdf)



Person	Age>10	Male?	Height > 55"
Alice	1	0	1
Bob	0	1	0
Carol	0	0	0
Dave	1	1	1
Erin	1	0	1
Frank	0	1	1
Gena	0	0	0
Harold	1	1	1
Irene	1	0	0
John	0	1	1
Kelly	1	0	1
Larry	1	1	1

# Recap: Lasso vs Ridge

- Model Assumptions
  - Lasso learns sparse weight vector
- Predictive Accuracy
  - Lasso often not as accurate
  - **Re-run Least Squares on dimensions selected by Lasso**
- Easy of Inspection
  - Sparse w's easier to inspect
- Easy of Optimization
  - Lasso somewhat trickier to optimize

# Recap: Regularization

- L2

$$\operatorname{argmin}_w \lambda \|w\|^2 + \sum_{i=1}^N (y_i - w^T x_i)^2$$

- L1 (Lasso)

$$\operatorname{argmin}_w \lambda |w| + \sum_{i=1}^N (y_i - w^T x_i)^2$$

- Multi-task


$$\begin{aligned} & \operatorname{argmin}_{w,v} \lambda w^T w + \lambda v^T v + \gamma (w - v)^T (w - v) \\ & + \sum_{i=1}^N (y_i^{(1)} - w^T x_i^{(1)})^2 + \sum_{i=1}^N (y_i^{(2)} - v^T x_i^{(2)})^2 \end{aligned}$$

- [Insert Yours Here!]


Omitting b &  
for simplicity

# Next Lecture: Recent Applications of Lasso

## Cancer Detection



## Personalization via twitter



Recitation on Wednesday: Probability & Statistics

Image Sources: <http://statweb.stanford.edu/~tibs/ftp/canc.pdf>  
<https://dl.dropboxusercontent.com/u/16830382/papers/badgepaper-kdd2013.pdf>